



### Cable Ties and Edge Clips for Panel Thickness 1.0 to 3.0 mm

With the Edge Clip family the bundled cables can be located either above or to the side of a fixing. In all two piece mounting ties, the edge clip moves freely along the tie. This allows the head of the tie to be rotated during mounting for installation in the ideal position.

Technical Table

Article-No.	Type	Length (L)	Width (W)	Bundle Ø max.	Min. Tensile Strength (N)	Material		Application Tool	Drawing
						Cable Tie	Foot Part		
Two piece, panel thickness 1.0 - 3.0 mm									
150-76090	<b>T30REC4A</b>	150	3.5	33.0	135	PA66HS	PA66HIRHS	1-3, 5	
150-76099	<b>T50ROSEC4A</b>	200	4.6	45.0	225	PA66HS	PA66HIRHS	1-5	
150-76080	<b>T30REC4B</b>	150	3.5	33.0	135	PA66HS	PA66HIRHS	1-3, 5	
150-76079	<b>T50ROSEC4B</b>	200	4.6	45.0	225	PA66HS	PA66HIRHS	1-5	
150-40591	<b>T50ROSEC5A</b>	200	4.6	45.0	225	PA66HS	PA66HIRHS	1-5	
150-40581	<b>T50ROSEC5B</b>	200	4.6	45.0	225	PA66HS	PA66HIRHS	1-5	
156-05903	<b>T50ROSEC9</b>	200	4.6	45.0	225	PA66HS	PA66HIRHS	1-5	
156-05904	<b>T50ROSEC10</b>	200	4.6	45.0	225	PA66HS	PA66HIRHS	1-5	
156-00010	<b>T50ROSEC21</b>	200	4.6	45.0	225	PA66HS	PA66HIRHS	1-5	
156-00011	<b>T50ROSEC22</b>	200	4.6	45.0	225	PA66HS	PA66HIRHS	1-5	
One piece, panel thickness 1.0 - 3.0 mm									
148-00200	<b>T50SOSEC12E</b>	160	4.6	35.0	180	PA66HS	PA66HS	1-5	
126-00000	<b>T50SOSEC13E</b>	160	4.6	35.0	180	PA66HS	PA66HS	1-5	

All dimensions in mm. Subject to technical changes.