

**I.D. sized for  
3/0 ga [81mm<sup>2</sup>]  
stranded cable**

**21/32" O.D.  
[16.7mm]  
(May vary due  
to shrinkage)**

**Hole sized for  
5/16" [M8] bolt**

**41/64"  
[16.3mm]  
Ref**

**2-1/2"  
[63.5mm]  
Ref**

**2-13/64"  
[55.9mm]  
Ref**

**Crimp  
Information**

**Cable size  
stamp**

**Sized for  
Pos. post**

**Polarity  
stamp**

<b>Property of</b> <b>QUICK CABLE</b> 3700 Quick Drive Frankeville, WI 53126 U.S.A. www.quickcable.com	<b>TITLE</b> <b>Die cast flag</b> <b>3/0 Ga. [81mm<sup>2</sup>]</b>
	<b>PART #</b> <b>4330P</b>
<b>Confidential and Proprietary Information</b>	
<b>Material &amp; Treatment</b> <b>High Conductivity</b> <b>Copper Alloy</b> <b>Matte Tin Plate</b>	<b>Drawing #</b> <b>4330P-Info</b>  <b>REV</b> <b>B</b>  <b>Sheet 1 of 1</b>

Rev	Date	ECN#	By	Description
<b>B</b>	5-21-10	2126	BS	update drawing
<b>A</b>	6-01-06	1295	JMH	Added color printing to tangs

<b>Drawn By</b> Jim H	<b>Date</b> 12/22/03	<b>Checked By</b> Mike E	<b>Scale</b> None
<b>Tolerances, unless otherwise noted</b> <b>Dimensions are reference only</b>			