



MATERIAL DATA

COMPONENT	MATERIAL	SPEC.
STRAP	POLYETHERETHERKETONE	MIL-P-46183 TYPE I
BUCKLE	POLYETHERETHERKETONE, 30% GLASS FILLED	MIL-P-46183 TYPE II, CLASS 3
BARB	301, 17-7, OR A-286 CRES	AMS 5519, 5525, 5528

MINIMUM STRAP LENGTH L: 8 INCHES

MAXIMUM STRAP LENGTH L: 1500 INCHES

MINIMUM LOCKING STRENGTH: 35 LBS

EXAMPLE PART NUMBER

CB9513 P5-15

LENGTH L IN INCHES
BASIC PART NUMBER

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES AND TOLERANCES ARE AS SHOWN BELOW. DIMENSIONAL TOLERANCES AND SYMBOLS PER ANSI Y14.5M-1982.

PROPRIETARY PARTS SHOWN IN THIS DRAWING ARE THE SUBJECT OF ISSUED UNITED STATES AND FOREIGN PATENTS AND PATENTS PENDING. UNAUTHORIZED REPRODUCTION AND/OR DISTRIBUTION OF THIS DRAWING IS SPECIFICALLY PROHIBITED.

GLICK BOND

CARSON CITY
NEVADA 89706

APPROVALS		DATE	TITLE				
ANGLES	±1°	DRAWN <i>DAC</i>	20APR04	TIE STRAP			
.XX	±.03	CHECKED <i>DOC/mtm</i>	20APR04	SIZE	CAGE CODE	DWG. NO.	REV.
.XXX	±.015	RELEASED <i>CGH</i>	29APR04	A	66530	CB9513	3
.XXXX	±.001	REVISED <i>DAC</i>	20APR04	SCALE	1/1	20APR04	SHEET 1 OF 1